




a complete act of
Balancing

Manufacturer & Exporter of Electronic Weighing Scale & Weigh Bridges

ENDEAVOUR INSTRUMENT PVT. LTD.



AN ISO 9001 - 2008 COMPANY



Plate Form, Table Top, Jewellery & Crane Scales

ENDEAVOUR INSTRUMENT PVT. LTD.

EDS/EPS/EPM



Features

- Sturdy MS square pipe structure provides equal Load distribution
- Small but sturdy structure for rugged use
- Optional weighing indicators
- Heavy duty structure
- Stainless steel top & Back Grill
- Overload Protection
- Optional MS Top Available

Specifications

Capacity	50kg 100kg 200kg 300kg 500kg
Readability	5g 10g 20g 50g 50g
Platform size	400 x 400 mm 500 x 500 mm 600 x 600 mm

ETS-B



Features

- Stainless Steel pan
- Battery provides up to 20 hours of continues use
- Standard dual display with front & pole display
- Tripple Accuracy Available
- Piece counting, Check weighing Available
- Complete SS moulded body

Specifications

Capacity	10kg 20kg 30 kg
Readability	1g 2g 5g 1/2/5 g
Pan Size	240 x 300 mm
Display	Red LED (0.56" high)
Power	220-240V AC; 50 Hz OR 6V 4.5 Ah Rechargeable battery
Op. Temp.	+10 to + 50°C
Optional	RS-232 Connection

FET-N



Features

- auto Calibration
- Power saving functon auto shutoff
- Responds quickly with accurate result.
- Standard dual display - Front display
- Application programs include : Piece counting
- percent weighing, accumulation, 4 unt conversion
- Piece counting, Check weighing Available
- Wind Shield is standard for 300 & 600g models
- Battery provides up to 20 hours of continues use.

Specifications

Capacity	300g
Readability	10mg
Pan Size	Ø 98mm
Display	LCD / LED
Power	AC Adaptor 6V or Rechargeable battery

CRANE SCALE



Features

- Big easy readable red LED display-height: 1.2"
- Accuracy: compatible to OIML class III
- Safety limit co-efficient: 4
- Gravity acceleration correction;so can be used anywhere in the world
- whole load, cell;so very strong and highly durable
- Low voltage indicator for battery voltage
- Power Saving function-auto shut off after 1.5 hrs of non use
- full function remote controller (optional)

Specifications

Capacity	1T 2T 3T 5T 10T 15T 20T
Readability	500g 1kg 1kg 2kg
Optional	Remote Controller
Display	1.2" red LED display
Power	rechargeable battery + AC Adapot
Display	125 % of maximum Capacity
OP.TEMP	1000 C/1.5m; 1200 c/1.6m; 1400 1.8m; 1600 2.0m;

Authorised Representative



ENDEAVOUR INSTRUMENT PVT. LTD.

Corp. Off. : 4th Floor, Mohini-II, Opp. Gandhigram Rly. Station, Nr. Sakar-I, Ashram Road, Ahmedabad-380 006. Gujarat, INDIA.
Ph.: +91-79-26582693-7 Fax : +91-79-26582107 Email at : - sales@endeavourweigh.com wevsite :- www.endeavourweigh.com

Factory : 45/3, Changodar Industrial Estate, Ahmedabad. Dist. Co-Op. Bank Road, Opp. S.T. Bus Stand, Sarkhej Bavla Highway, Changodar - 382 213. Ta. Sanand, Dist.: Ahmedabad (Gujarat)

Domestic Branches :- BARODA • VAPI • GANDHIDHAM • KOTA • PUNE Overseas Branches :- DUBAI • OMAN • KENYA • UGANDA • TANZANIA